

UVS

With ADEMCO's new Universal Voice System (UVS), you'll increase the value of every sale and add an entirely new level of comfort and protection to your customer's lives. The Universal Voice Control Module (UVCM) connects quickly and easily to a VISTA control and one standalone intercom station (UVST)—expanding into a powerful indoor/outdoor home communication system*.

Two-way audio verification technology significantly reduces false alarms, and lifestyle-enhancing convenience features including an intercom, baby monitor, and speakerphone simplify your customer's lives while providing increased peace of mind. The optional outdoor cover (UVST/ODC) fits over the UVST station for use as an entranceway visitor screening station.

* with the addition of additional intercom stations (up to seven)



Two-Way Communication System

FEATURES:

Audio Alarm Verification:

- Two-way voice communication with the central station in the event of an alarm

Intercom:

- Broadcast a message to all stations in the home
- Hold a private conversation between two stations
- With the outdoor station, answer the front door without opening it to strangers
- With a touchtone phone, the consumer can conduct a two-way voice conversation with someone on the premises

Speakerphone:

- Broadcast the ringing of your phone over the stations
- Answer calls from any station
- Transfer a caller to another inside station
- Hands free conversation between stations
- Hands free conversation on incoming phone calls
- Supports call waiting

Audio System:

- Any station can become a baby monitor
- Connect to a stereo input for music throughout the home
- Security messages annunciate over the stations with a 4286 VIP Module

UVS

SPECIFICATIONS:

Physical

UVST Dimensions:

- 5-1/8" H x 2-3/4" W x 1-1/2" D

UVCM Dimensions:

- 10" H x 10" W x 3" D

Electrical

UVST Ratings:

- Operating Voltage: 9VDC to 14VDC
- Current Drain: 10mA idle/70mA active

- Wire Run Length: Home run 22AWG, 4 conductor cable back to UVCM, 200 feet maximum

- Temperature Range: 14°F to 140°F (-10°C to +60°C)

- Maximum Stations: Supports up to seven stations total. Up to two stations may be used outside

UVCM Ratings:

- Operating Voltage: 10VDC to 14VDC
- Current Drain: 60mA idle/110mA active

**Two-Way
Communication
System**

ORDERING:

Part No.	Description
UVS	Universal Voice System (consists of (1) UVCM AND (1) UVST)
UVCM	Control Module
UVST	Universal Voice Station
UVST/ODC	Outdoor Cover
4286	VISTA Interactive Phone Module

L/UVS/D Rev. 6/03

165 Eileen Way, Syosset, NY 11791
Copyright ©2002 Pittway Corporation
ADEMCO is an ISO9001 Registered
Company

ADEMCO
A Honeywell Company